

## FORMALDEHYDE EMISSION STATEMENT

### Medium Density Fibreboard (MDF)

Carter Holt Harvey Woodproducts Australia Pty Ltd (CHH) manufactures 'E1' and 'Eo' MDF at its Oberon MDF plant, in both standard and moisture resistant grades.

These products are manufactured to comply with the relevant formaldehyde emission potential requirements stipulated by AS/NZS1859.2: 2004 [Reconstituted wood-based panels – Dry processed fibreboards], notably with a maximum allowable formaldehyde emission of 1.0 and 0.5 mg/L for 'E1' and 'Eo' respectively.

Samples of the products are routinely submitted to an independent NATA registered laboratory for formaldehyde emission testing in accordance with AS/NZS4266.16 [Reconstituted wood-based panels – Methods of test - Method 16 - Formaldehyde emission - Desiccator method].

CHH understand that the Green Star building program (Office Interiors), as developed by the Green Building Council of Australia, currently awards 1 point for the use of MDF with formaldehyde emission levels that meet the above standard.

This statement is confirmation that all MDF products manufactured by CHH meet the standard and are therefore eligible for points under the Green Star building program.



Robert Alcock  
Technical Manager  
CHH Woodproducts Australia – Oberon MDF

October 2009