

# HiLight® ThreeBar













HiLight® ThreeBar is an ideal low profile option when stair manufacture allows for recessing of the stair treads. The sleek design and excellent safety rating of the HiLight® ThreeBar provides seamless integration with its environment.

When the asthetic demands clean lines and crisp design - HiLight® ThreeBar is the perfect solution.

Available with P5 rated grey, black or safety yellow carborundum inserts, the HiLight® ThreeBar provides maximum safety in a minimal design.

Recessed into the stair tread, and fixed by adhesive or concealed screws, HiLight® ThreeBar is NCC compliant and meets AS1428 luminance requirements.


Manufactured from 5mm hard tempered anodized aluminium, it's perfect for areas with high foot traffic without compromising on aesthetics.

#### **KEY FEATURES**

- Conforms to all aspects of the relevant safety and public access
- Available in 3 insert colours: black, safety yellow and grey.
- Ideal choice for seamless design, where safety is incorporated within the stair tread.
- 5 Year CTA manufacturers warranty.
- P5 safety rating, the highest in the industry.

#### HILIGHT® THREEBAR FEATURES





#### **INSTALLATION**

A recess of 5mm deep x 52mm wide is required, glued direct onto hard surfaces or screwed via concealed fixing points. Suitable for both internal and external environments.

#### PRODUCT OPTIONS

MODEL	SLIP RATING	INSERT	PRODUCT CODE
Recessed	P5	Carborundum	UM070-SNCI-XXX
Recessed	P5	Egress	UM070-SNCI-PL-XXX

Where XXX = insert colour (see below). Also available as a Black extrusion (UM070160)

## **MATERIAL**

Manufactured from a 5mm hard tempered anodized aluminium extrusion carrying 3 carborundum strip inserts for heavy traffic applications.

#### **APPLICATIONS**

HiLight® ThreeBar is ideal in areas requiring excellent wear resistance and high end aesthetics such as, restaurants hotel lobbies, and areas subject to high foot traffic.

Ideally HiLight® ThreeBar is included in the manufacture of the stair treads, however can be applied as a retro-fit option. This is provided routing of the stair tread is practical.

#### **DIMENSIONS**

50mm wide and 5mm thick -3.6m or supplied to length.

#### COMPLIANCE

All CTA products conform with the requirements of the Australian standards and are tested by NATA certified labs.

Please consult with CTA for relevant test reports:

- AS1428:2009 Design for access and mobility
- AS4586:2013 Slip resistance classifications for new pedestrian surface materials
- NCC National Construction Codes

#### LUMINANCE CONTRAST

Please view the CTA Luminance Brochure for details or contact your CTA representative to discuss or request an onsite luminosity test.

#### WARRANTY

CTA provides a comprehensive warranty, in accordance with our published warranty statement which can be viewed on cobbletac.com.

### CTA COMPLETE CARE MAINTENANCE

Asset owners have a Duty of Care responsibility to maintain access product within design performance parameters. CTA offers a fully integrated maintenance program which includes regular scheduled maintenance and replacement of worn components where necessary. Please contact your CTA representative for information on our "Complete Care Program."

#### CTA INSTALLERS

CTA's accredited installers are available to do the installation work for you - with short turnaround times and guaranteed workmanship. Our installation team is the largest and most experienced in the nation, so you can rest assured you are in safe hands.

#### MORE INFORMATION

Product Installation, list of Approved Products and Material Safety Data Sheets are available on request.

#### HILIGHT® SAFETY INSERT SYSTEM

The HiLight® family of safety stair edging utilises a common insert system. Comprised of a 10mm wide Carborundum P5 rated insert in three colours, these inserts offer the specifier the ability to mix colours to create the desired effect. A photo-luminescent option is also available. Please contact CTA for product images and to request a sample in the colours of your choice.

	Carb	Egress
AS4586:2013 Rating	P5	P5
Material	Carborundum	Carborundum & Photo-Luminescent
Colours	Yellow / Grey / Black	Yellow / Grey / Black
Warranty / Life Expectancy	5 Years / 10+ years	5 Years / 10+ years
	,	·
VEL L OW/112	ODEV155	DI A 01/160

## CALL CTA ON 1300 282 282

