



GraniTac[®]



GraniTac[®] tactile pavers, manufactured from natural granite, offer the outstanding durability of granite and combine legendary durability with a wonderful natural appearance.

Architects and landscape designers will appreciate the breadth that GraniTac[®] adds to their tactile product choice. Project managers will appreciate a product which is easily incorporated without interrupting construction timelines. Building managers will appreciate a product that is permanent, needing little if any maintenance over many years.

And while GraniTac[®] tactile indicators are ideal for the most demanding external environments, they can also be used to complement modern internal designs.

Also available in GraniTac[®] Select.

KEY FEATURES

- Available in both hazard (stud) and directional (rib) profiles
- Very high P5 slip resistance rating, exceeding AS4586 requirements in wet and dry conditions
- Meets AS1428 tactile design requirements
- Colour and size stable
- Standard installation using normal paving practices with 3-5mm grouting between the pavers
- Available with 20mm base, 40mm for GraniTac Select.



PRODUCT OPTIONS

COLOUR OPTION	SIZE	PRODUCT CODE HAZARD STUD	PRODUCT CODE DIRECTIONAL RIB
Ivory	300 x 300 x 20mm base	HGT108CT	DGT108CT
Yellow	300 x 300 x 20mm base	HGT112CT	DGT112CT
Grey	300 x 300 x 20mm base	HGT155CT	DGT155CT
Black	300 x 300 x 20mm base	HGT160CT	DGT160CT
Ivory over Blue Stone	300 x 300 x 40mm base	HGTS108CT	DGTS108CT
Blue Stone over Ivory	300 x 300 x 40mm base	HGTS135CT	DGTS135CT

Also available in 400 x 400mm on request

MATERIAL

Natural granite stone. GraniTac® tactile indicators have inherited the benefits of granite making them the most hard wearing and reliable tactile products on the market.

APPLICATIONS

GraniTac® tactile indicators are designed for permanent installation into pavements, paths and ramps. Ideally suited to challenging external applications, they can also be installed internally into concrete, tiled or paved floors.

DIMENSIONS

Standard 300mm x 300mm dimensions and 5mm stud height, GraniTac® has a 20mm base, 40mm for GraniTac® Select. Also available in 400mm x 400mm format on request.

INSTALLATION METHOD

GraniTac® Tactiles must be laid level with the surrounding surface so that the tactile stud stands proud. A recess (25mm or 45mm for GraniTac® and GraniTac® Select respectively) must be provided, the tactiles are laid into this recess using an approved adhesive applied with a suitable square notched trowel. GraniTac® Select being 40mm thick can be laid as a paver on a suitable base of sand/cement. Floor traffic should be avoided ideally for 48 hours or at least for 24 hours after installation. See Product Installation sheet for full instructions.


PRODUCT DATA

Dimensions (Standard)	300 x 300 x 20+5
Dimensions (Select)	300 x 300 x 40+5
Weight (Standard)	5.5 kg
Weight (Select)	9.5 kg
AS1428 Compliant	Yes
AS4586 (Hazard)	77 / P5
AS4586 (Directional)	68 / P5
NCC Compliant	Yes
Materials	Natural Granite
UV Stable	Yes
Warranty	10 Years
Life Expectancy	25+ years
Indoor Use	If suitable
Outdoor Use	Yes

COLOURS



INSTALLATION



COMPLIANCE

All CTA products conform with the requirements of the Australian standards and are tested by a NATA certified laboratory. Please consult with CTA for relevant test reports:

- AS1428:2009 Design for access and mobility
- AS4586:2013 Slip resistance classifications for new pedestrian surface materials
- NCC - National Construction Codes

LUMINANCE CONTRAST

Please view the CTA Luminance Brochure for details or contact your CTA representative to discuss or request an onsite luminosity test.

WARRANTY

CTA provides a comprehensive warranty, in accordance with our published warranty statement which can be viewed on www.ctagroup.com.au

CTA COMPLETE CARE MAINTENANCE

Asset owners have a Duty of Care responsibility to maintain access product within design performance parameters. CTA offers a fully integrated maintenance program which includes regular scheduled maintenance and replacement of worn components where necessary. Please contact your CTA representative for information on our "Complete Care Program."

CTA INSTALLERS

CTA's accredited installers are available to do the installation work for you – with short turnaround times and guaranteed workmanship. Our installation team is the largest and most experienced in the nation, so you can rest assured you are in safe hands.

MORE INFORMATION

Product Installation, list of Approved Products and Material Safety Data Sheets are available on request.

CALL CTA ON 1300 282 282
TO ARRANGE A MEETING WITH A SALES CONSULTANT

VICTORIA | NEW SOUTH WALES | QUEENSLAND | WESTERN AUSTRALIA

