



# SafeLine® Step









SafeLine® Step is a hybrid alternative that combines the best features of the ProStep® and PosiTread® ranges. With the durable, P5 safety of the ProStep® Classic, and the clean, minimal aesthetic of the PosiTread range.

Available as both an angle and a tread, the SafeLine® Step uses the SafeLine® range of strip insert safety tapes, which are manufactured from a unique combination of aluminium oxide and a thick plastic carrier to provide a flexible yet durable anti-slip solution.

Suitable for both internal and external use, SafeLine® Step provides a cost effective safety stair nosing that doesn't compromise on aesthetics.

Supplied cut to length with the SafeLine® Tape applied, DIY installation is easy to achieve with a suitable adhesive.

### **KEY FEATURES**

- Easy to install with no fuss ideal for DIY applications
- Provide an P5 safety rating, the highest in the industry
- Conforms to all aspects of the relevant safety and public access standards
- Supplied to length up to 3.6m
- Available in 6 colours including hazard, and luminescent
- Meet NCC requirements

MAY 2015

#### SAFELINE® STEP PROFILE

Available in 10mm face A Series, and SafeLine tread (both NCC compliant) and 30mm full face Standard.



# **PRODUCT OPTIONS**

MODEL	SLIP RATING	COLOUR	PRODUCT CODE
SafeLine Tread	P5	Natural Silver	UMD080-XXX
		Black	UMD081-XXX
10mm SafeLine Angle	P5	Natural Silver	UMD075-XXX
		Black	UMD076-XXX
10mm SafeLine Angle with Ramp	P5	Natural Silver	UMD077-XXX
		Black	UMD078-XXX
30mm SafeLine Angle	P5	Natural Silver	UMD085-XXX
		Black	UMD086-XXX

Where XXX = Insert colour (see right)

#### **MATERIAL**

Manufactured from anodised aluminium extrusions and SafeLine® inserts – a unique combination of aluminium oxide and a thick plastic carrier. Also available in Anodised black extrusion.

#### **APPLICATIONS**

SafeLine® Step stair nosing is particularly suitable for light duty pedestrian traffic in internal and external flooring surfaces prone to water or oil spillage.

# **INSTALLATION**

Supplied to length for installation with a suitable adhesive.

# **COLOURS**



#### **DIMENSIONS**

Angle with 10mm or 30mm face edge and 55mm wide. 50mm wide SafeLine safety tread inserts. Supplied to length up to 3.6m.

#### COMPLIANCE

All CTA products conform with the requirements of the Australian standards and are tested by a NATA certified laboratory. Please consult with CTA for relevant test reports:

- AS1428:2009 Design for access and mobility
- AS4586:2013 Slip resistance classifications for new pedestrian surface materials
- NCC National Construction Codes

#### **LUMINANCE CONTRAST**

Please view the CTA Luminance Brochure for details or contact your CTA representative to discuss or request an onsite luminosity test.

# **WARRANTY**

CTA provides a comprehensive warranty, in accordance with our published warranty statement which can be viewed on www.ctagroup.com.au

# CTA COMPLETE CARE MAINTENANCE

Asset owners have a Duty of Care responsibility to maintain access product within design performance parameters. CTA offers a fully integrated maintenance program which includes regular scheduled maintenance and replacement of worn components where necessary. Please contact your CTA representative for information on our "Complete Care Program."

#### **CTA INSTALLERS**

CTA's accredited installers are available to do the installation work for you – with short turnaround times and guaranteed workmanship. Our installation team is the largest and most experienced in the nation, so you can rest assured you are in safe hands.

#### MORE INFORMATION

Product Installation, list of Approved Products and Material Safety Data Sheets are available on request.





