



# Entrymaster® Classic Matting



Entrymaster® Classic has proven itself time and time again as an excellent performing polypropylene entrance mat. Entrymaster® has a rubber-reinforced profile to prevent the pile crushing even in the highest traffic areas.

When you need a quality commercial surface mounted entry mat to keep your entrance area clean and safe, Entrymaster® Classic is the perfect choice. Entrymaster® Classic features a 'Water Dam' edge design which retains dirt and water, ensuring the area surrounding the mat remains clean and dry.

Entrymaster® Classic is easily cleaned by sweeping, vacuuming or hosing, dries quickly and the durable polypropylene will not fade, rot or stain. The cleated back minimises movement on most surfaces.

## KEY FEATURES

- Ideal for high traffic areas
- Meets flammability standards
- Excellent dirt and water retention, and easily cleaned.
- Durable polypropylene will not rot, fade or stain and dries quickly
- Available in Charcoal or Bluestone
- 5 Standard sizes
- Anti-static, safe for use in sensitive areas rating 1.2KV



**MATERIAL**

Manufactured from durable Polypropylene with moulded rubber edges which will not tear or curl.

**APPLICATIONS**

Very hard wearing product which performs well in all high traffic applications such as shopping centres and educational institutions.

**DIMENSIONS**

Please see standard sizes below, these sizes include edging.

**PRODUCT OPTIONS**

SIZE	COLOUR	PRODUCT CODE
580 x 870mm	Charcoal	STRL200-155-6x9
	Bluestone	STRL200-135-6x9
860 x 1450mm	Charcoal	STRL200-155-9x15
	Bluestone	STRL200-135-9x15
1140 x 1720mm	Charcoal	STRL200-155-12x18
	Bluestone	STRL200-135-12x18
1140 x 5950mm	Charcoal	STRL200-155-12x60
	Bluestone	STRL200-135-12x60
1800 x 5950mm	Charcoal	STRL200-155-18x60
	Bluestone	STRL200-135-18x60
1140mm - cut to length	Charcoal	STRL200-155-12C
	Bluestone	STRL200-135-12C
1800mm - cut to length	Charcoal	STRL200-155-18C
	Bluestone	STRL200-135-18C

**COLOURS**

- CHARCOAL
- BLUESTONE

**COMPLIANCE**

All CTA products conform with the requirements of the Australian standards and are tested by a NATA certified laboratory. Please consult with CTA for relevant test reports:

- AS1428:2009 Design for access and mobility
- AS4586:2013 Slip resistance classifications for new pedestrian surface materials
- NCC - National Construction Codes

**LUMINANCE CONTRAST**

Please view the CTA Luminance Brochure for details or contact your CTA representative to discuss or request an onsite luminosity test.

**WARRANTY**

CTA provides a comprehensive warranty, in accordance with our published warranty statement which can be viewed on [www.ctagroup.com.au](http://www.ctagroup.com.au)

**CTA COMPLETE CARE MAINTENANCE**

Asset owners have a Duty of Care responsibility to maintain access product within design performance parameters. CTA offers a fully integrated maintenance program which includes regular scheduled maintenance and replacement of worn components where necessary. Please contact your CTA representative for information on our "Complete Care Program."

**CTA INSTALLERS**

CTA's accredited installers are available to do the installation work for you – with short turnaround times and guaranteed workmanship. Our installation team is the largest and most experienced in the nation, so you can rest assured you are in safe hands.

**MORE INFORMATION**

Product Installation, list of Approved Products and Material Safety Data Sheets are available on request.

**CALL CTA ON 1300 282 282**  
**TO ARRANGE A MEETING WITH A SALES CONSULTANT**  
 VICTORIA | NEW SOUTH WALES | QUEENSLAND | WESTERN AUSTRALIA

